

THANK YOU FOR PURCHASING
THE INSTATRUNK
FOR THE JEEP WRANGLER

instaTrunk

Maximum Security Storage in an Instant

INSTALLATION INSTRUCTIONS
Part Number: MD1341
Jeep Wrangler 86+

PLEASE READ ALL INSTALLATION INSTRUCTIONS BEFORE PROCEEDING

1. If weatherstrip has not already been applied to the Trunk's top panel, remove the length of foam weatherstrip from the hardware pack. This gasket forms the protective seal between the instaTrunk and your tailgate. Peel off the backing from the adhesive and attach the weatherstrip continuously along the outer, contoured edge of the Trunk's top panel.
2. The instaTrunk for Wranglers is pre-cut to work with the rear seat restraint attachments.
3. Open the tailgate of your Wrangler and lean the rear seatback forward (The lever is in the lower left corner).
4. Lift the instaTrunk above the rear cargo area and lower it into position behind the rear seat, between the rear wheel wells. The notched channel in the back panel will fit smoothly against the seat belt attachments with the plastic restraint covers.
5. The indented, contoured top panel of the Trunk should be flush with the tops of the wheel wells and level, with the back panel at a right angle to the floor of the cargo space.
6. The instaTrunk is designed to fit snugly in place. On some vehicles, extra padding is located behind the carpeting. It may be necessary to remove this padding for the Trunk to fit properly.
7. Work the Trunk into position and adjust the carpeting to fit smoothly around the top panel prior to completing installation.
8. Check the fit by closing the tailgate. The weatherstrip on the Trunk should form a seal with the inner surface of the tailgate. Adjust the position of the instaTrunk, if necessary, to butt up against the tailgate.
9. Your instaTrunk is pre-drilled for attachments to the inner wheel well panels and six self-tapping screws are provided. These screws may be installed using a center punch and hand screwdriver, but a power drill with a phillips driver bit is recommended.
10. With your instaTrunk in proper position, drive the self-tapping screws through the pre-punched installation holes in the Trunk and securely into the side panels of the cargo area.

CAUTION: Do not drill into the floor of your Wrangler for the installation of the instaTrunk. The Trunk must be securely and properly installed in the vehicle during vehicle operation.

REAR SEAT OPERATION: Your rear seat remains completely functional with the instaTrunk installed. There's an additional rear seat release lever IN FRONT OF THE SEAT BACK, on the driver's side.

WARRANTY
Markets Direct Inc., the manufacturer of the instaTrunk, warrants this product to be free of defects on workmanship and materials for 90 days from the date of purchase. Proof of purchase is required for all warranty claims. Replacement or repair of warranted products is at the sole discretion of Markets Direct.

The instaTrunk is a quality automotive accessory from:

Markets Direct, Inc.
P. O. Box 12168 Dallas, Texas 75225
(214) 368-5357

instaTrunk is a registered trademark of Markets Direct, Inc.
instaTrunk is a patented product (Patent No. 4,938,519)

All rights reserved
Jeep is a registered trademark of Chrysler Corp.