



WWW.SMITTYBILT.COM

Installation Instructions

6" Fender Flares

(Part #17190)

1997-2006 Jeep TJ

Note: Please read instructions entirely before installing this product.

Parts Included	Qty	Parts Included	Qty
Driver Front Flare	1	Snap Bases	28
Passenger Front Flare	1	Snap Covers	28
Driver Rear Flare	1	Washers	28
Passenger Rear Flare	1	M5 x 32 Bolt	28
Flare Extension	2	M5 Nut	28
Rubber Fender Trim		Rubber Spacers	

Prior to installation:

Pre-fit all flares before you attempt to install. If you plan on painting your Fender Flares it must be done prior to installation. All surfaces must be cleaned using a scouring pad such as Scotch Brite and prepped using an adhesion promoter. Follow all specifications required by the paint manufacturer. As you remove factory parts set them aside safely for later use.

Remove the Factory Flares from vehicle

- Step 1:** Start with the rear fender flare. Remove the rear wheel well cowl by prying back the christmas tree fasteners.
- Step 2:** Locate and remove the bolts holding the factory flares on the vehicle.
- Step 3:** Repeat on the other side of vehicle.
- Step 4:** Proceed to the front and remove the marker lights on the factory flare. Locate and remove the bolts holding the factory flare on the vehicle. Repeat on the other side of vehicle

Install Rubber Trim

- Step 1:** Locate the supplied rubber trim. Starting at one end of the flare, push the trim onto the outer edge of the flare (See: Fig A)
- Step 2:** Continue pressing the rubber trim onto the flare. Push on approximately 4" then hold in place. (See: Fig B) Continue on in this manner until you have gone completely around the flare. This will take some time but once you master the technique it will precede quickly. Cut rubber trim to length as installed. Repeat this process for the remaining flares



(Fig A)



(Fig B)



(Fig C)

For Technical Support/Warranty Information please call 310-762-9944

Smittybilt, 400 West Artesia Blvd, Compton, CA 90220



WWW.SMITTYBILT.COM

Installation Instructions

6" Fender Flares

(Part #17190)

1997-2006 Jeep TJ

Install Flares and Mud Guards

- Step 1:** Start with the front fender flares. Place a clear snap cap base on the screw and place the screw through the mounting hole in the flare. Place a 7mm spacer on the screw from the backside of the flare. If you have a large gap, use two spacers. Repeat until all screws have been installed on the flare. (See: Fig D)
- Step 2:** Hold the flare against the Vehicle and insert the screws through the factory holes in the fender. Place a flat washer and start the nuts on the screws. Do **NOT** tighten any nuts until all nuts have been installed and the fender trim rubber has been properly aligned. ***CAUTION:*** Do **NOT** over tighten the screws.
- Step 3:** Reinstall the factory marker light into flare, using the factory hardware.
- Step 4:** Repeat on the other side.
- Step 5:** Proceed to install rear flares. Repeat Steps 1 & 2 above. Use the supplied nuts in positions that do not have a threaded insert in the vehicle body.
- Step 6:** Attach Mud Guards to the vehicle using the factory hardware previously removed from vehicle.
- Step 7:** Place the snap cap cover over the mounting screws and cap base and press firmly into place. Repeat process for the remaining caps.

Compliment your flares with other Smittybilt products like, bumpers, winches and softgoods



(Fig D)



For Technical Support/Warranty Information please call 310-762-9944

Smittybilt, 400 West Artesia Blvd, Compton, CA 90220



WWW.SMITTYBILT.COM

Installation Instructions

6" Fender Flares

(Part #17190)

1997-2006 Jeep TJ

Limited Warranties

Smittybilt's products are covered under the following limited warranties only. Note that the duration of the limited warranty differs according to the material and finish of the product purchased. Subject to the duration and conditions of the limited warranty stated below, Smittybilt warrants to the original retail purchaser that its products are free from defects in material and workmanship. All other warranties and representations express or implied, are hereby disclaimed, including fitness for merchantability and buyer's intended use or purpose. All parts are sold "AS IS" except for the limited warranties granted herein. Buyer assumes all risks as to the selection, suitability and performance of all goods and products selected. This limited warranty does not cover damage or impairment in any part due to misuse, improper installation, accident or contact with on-road or off-road hazards, product modification, improper or inadequate cleaning and/or maintenance. Smittybilt is not responsible for items damaged during shipping. This warranty is not transferable from the original buyer. For the original Buyer to be eligible for the limited warranty coverage, the Buyer must provide proof of purchase. Smittybilt strongly recommends returning the warranty registration card.

Customer's remedy hereunder shall be limited only to repair or replacement (at Smittybilt's option) of any defective part(s) returned to Smittybilt at customer's expense. The determination of whether or not a returned part is defective or subject to coverage under the limited warranties stated herein shall be made at Smittybilt's sole discretion.

1. Limited Three (3) Year Pro-Rata Warranty on Fender Flares -

Smittybilt Fender Flares carry the foregoing limited repair or replacement warranty for a period of three (3) years against workmanship and defects in the material from the date of purchase.

To assure product quality, Smittybilt reserves the right to change product design, material, specification and finishes without prior notice to customers. This limited warranty gives you specific legal rights and you may also have other rights, which may vary from state to state. Some states do not allow limitations on how long an implied warranty lasts, so the above limitations may not apply as to you. Also, some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. Smittybilt reserves the right to discontinue product lines and substitute products, or provide other remedies than those listed in this limited warranty for those discontinued products.

Warning

Rollover and other types of vehicle accidents may result in serious injury or death to you, your passengers and others sharing the road. Smittybilt accessories are decorative and are not intended to reduce or avoid injury or damage in the event of an accident. The weight and location of Smittybilt accessories may affect your vehicles' handling, stability and performance, creating an increased risk of accident or rollover. Before installing any accessory, check state laws and assure that the accessory will not obscure any lights or interfere with proper operation on your vehicle's safety equipment. Consult your owner's manual and the Smittybilt instructions, or additional safety information. Smittybilt products, nor the warnings contained herein, are not a substitute for your safe driving. Don't drink and drive, always use seat belts and don't drive faster than conditions permit.

For Technical Support/Warranty Information please call 310-762-9944

Smittybilt, 400 West Artesia Blvd, Compton, CA 90220