

INSTALLATION INSTRUCTIONS

PART No.

FB21120

Jeep® '18-Current JL Wrangler & '20 JT Gladiator
Headlight Guards



REQUIRED TOOLS

Body Clip Remover
10mm Socket
4mm Allen

KIT CONTAINS

Headlight Guard (Left)
Headlight Guard (Right)
Button Head Bolt

QTY

1
1
6

INSTALLATION INSTRUCTIONS

PART No.

FB21120

Jeep® '18-Current JL Wrangler & '20 JT Gladiator
Headlight Guards

1) REMOVE YOUR GRILL

Open your vehicle's hood.

With a body clip remover, remove the 6 body clips located just above the grill.



Remove the grill by gently and evenly pulling at its bottom, releasing the 6 white retaining clips.



2) REMOVE HEADLIGHT HARDWARE

With a 10mm socket, remove the 3 bolts securing your headlights to the vehicle.



3) INSTALL GUARDS

Place the corresponding guard over the light and into the 3 bolt slots. With a 4mm Allen key, secure the guard and light with 3 of the included button head bolts.



Repeat on the opposite side.



INSTALLATION INSTRUCTIONS

PART No.

FB21120

**Jeep® '18-Current JL Wrangler & '20 JT Gladiator
Headlight Guards**

4) REASSEMBLE YOUR VEHICLE

Begin reassembling your vehicle by starting with pressing and snapping your grill back into place.

Replace the body clips.

Close the hood.

**5) ENJOY YOUR NEW FISHBONE OFFROAD
HEADLIGHT GUARDS!**

