

GOBI JEEP JK 4DOOR WRANGLER STEALTH ROOF RACK SPECIFICATIONS

PRODUCT TYPE Jeep JK 4 Door vehicle luggage roof rack with

sun roof opening.

WEIGHT 88 lbs (39.92kg)

LENGTH 90" (2.29M)
WIDTH 54" (1.37M)

HEIGHT Front Light Bar 6" (152.4mm) Roof Rack 3" (76.1mm)

PAINT Black textured semi gloss Powder coat with

Gray epoxy anti-rust undercoat

USABLE CARGO 16.26 sq.ft. (1.51m2) (with sun roof opening)

SPACE Additional cargo space of 10.4 sq.ft.(.97m2) can be

added with a sun roof insert available upon request.

Sun roof insert load limit 150lbs. (68.04kg)

ROOF RACK STATIC

LOAD LIMIT

800 Lbs. (362.87kg)

ROOF RACK DRIVING

LOAD LIMIT

300 lbs (111.97kg)

CARGO DECK 34" 9 gauge expanded metal welded in place

FRAME 1-1/4" (31.75mm) 14 gauge, 1.0" (25.4mm) 16 gauge welded tubular frame

with 2 1-1/8" O.D. welded in accessory attachment cross bars

VEHICLE

ATTACHMENT

1- Front light bar attached to base of OEM windshield outer frame. Used to support front end of Roof Rack by means of 4-3/8" carrage bolts. Black powder coated with Gray epoxy anti-rust undercoat.

2- Rear 1/4" Formed steel Support towers black powder coated with Gray epoxy anti-rust undercoat attached to OEM Body and Frame.

1- Rear support roll bar attached to Support Towers and underside of roof rack. Black powder coated with Gray epoxy anti-rust undercoat.

NO DRILLING.

GOBI JEEP RANGER 4 Place front light bar for use with up to 5"x7" Rectangular Lights or

FRONT LIGHT BAR 6"-8" Round Lights

GOBI JEEP STEALTH 4 Place front light bar for use with up to 2.5" x 6" oval or

FRONT LIGHT BAR Rectangular off road lights.

REAR LIGHT BAR 2 independent rear light tabs for use with up to

2.5" x 6" off road lights

HARDWARE Stainless Steel and Grade 8

HEIGHT OF VEHICLE WITH From the vehicle top to the highest point of the

GOBI RANGER ROOF RACK GOBI Ranger Rack is 79.5"

HEIGHT OF VEHICLE WITH From the vehicle top to the highest point of the

GOBI STEALTH ROOF RACK GOBI Stealth Rack is 78" (1.98M)



GOBI JEEP JK 4DOOR WRANGLER STEALTH ROOF RACK SPECIFICATIONS

